



P.C.B Layout

Dimension

Position	A	B	C
06	13.92	10.52	5.08
08	16.46	13.06	7.62
10	19.00	15.60	10.16
12	21.54	18.14	12.70
14	24.08	20.68	15.24
20	31.70	28.30	22.86
22	34.24	30.84	25.40
24	36.78	33.38	27.94
26	39.32	35.92	30.48
30	44.40	41.00	35.56
36	52.02	48.62	43.18
40	57.10	53.70	48.26
44	62.18	58.78	53.34
50	69.80	66.40	60.96
60	82.50	79.10	73.66
62	85.04	81.64	76.20
72	97.74	94.34	88.90
86	115.52	112.12	106.68
100	133.30	129.90	124.46

Electrical Characteristics:

Current Rating: 2 AMP
 Insulator Resistance: 1000M Ohm min. At DC 500V DC
 Contact Resistance: 30m Ohm max. At DC 100mA
 Withstanding Voltage: 1000V AC / rms 50Hz for 1 minute
 Operating Temperature: -45°C~+105°C

Material:

Housing: Glass filled PBT UL94V-0
 Contacts: Brass or Phosphor Bronze
 Plating: Contact Gold and Dip Tin over Nickel

General description of ordering code

FAMILY	ROWS	POSITIONS	PLATING	TYPE	SOLDER	OPTION
ED254	2	XX	F [gold flash]	A [straight]	0 [pcb tht]	0 [without ears]
	1		G [gold 10u']		1 [wire solder]	1 [with ears]



euro-conn



UNITS: mm

SHEET SIZE: ISO A4

SCALE: ----

> 0 ~ 3

> 3 ~ 18

> 18 ~ 50

> 50 ~ 120

± 0.12

± 0.15

± 0.3

± 0.5

! I prodotti e le caratteristiche possono cambiare senza preavviso.
 The products and their features may change without notice.

CARD EDGE