



## Technical Specs:

Insulator:	Black glass filled polyester PPS-GF30-FR
Flammability:	UL 94V-O
Sleeve:	Brass
Contact clip(6 finger):	Beryllium copper(C17200)
Accepted pin:	Ø0.70 to 0.90mm,0.635mm
Forces:	(polished steel gauge Ø0.76mm)
--Insertion	2 N typ
--Withdrawal	1 N typ
Mechanical life:	min500 cycles
Rated current:	3A
Contact resistance:	max 10mΩ
Dielectric resistance:	Min 1000V RMS

## General description of ordering code

FAMILY	PITCH	N° ROWS	N° PIN P.R.	VERSION	CLIP PLATING	HEIGHT	OPTION	PACKAGE	SPECIAL
<b>FH</b>	<b>254</b>	- <b>2</b>	<b>XX</b>	<b>D</b> [straight]	<b>F</b> [flash gold]	<b>070--</b>	<b>00</b> [standard]	<b>T</b> [tube]	<b>R</b> [Round Pin]

**T** [tin]



**euro-conn**



**UNITS:** mm

**SHEET SIZE:** ISO A4

**SCALE:** ----

> 0 ~ 3

> 3 ~ 18

> 18 ~ 50

> 50 ~ 120

± 0.12

± 0.15

± 0.3

± 0.5

! I prodotti e le caratteristiche possono cambiare senza preavviso.  
The products and their features may change without notice.

**MACHINE HEADER**