



**SPECIFICATIONS**  
 Rated Current:3.0AMP  
 Contact Resistance:20mΩ Max  
 Withstand Voltage:1000V AC/DC  
 Insulation Resistance:1000MΩ Min  
 Operation Temperature:-40°c to +105°c

Contact Material:Brass  
 Contact Plating:Au Over Ni  
 Insulator Material:Polyester(UL94V-0)  
 Standard: PBT  
 Max.Processing Temp: 180°C for 30-60 seconds  
 (200°C for 10 seconds)

**General description of ordering code**

| FAMILY    | PITCH      | TYPE             | HEIGHT     | COLOR            |
|-----------|------------|------------------|------------|------------------|
| <b>MJ</b> | <b>254</b> | <b>A</b> [open]  | <b>085</b> | <b>N</b> [black] |
|           |            | <b>C</b> [close] |            | <b>R</b> [red]   |
|           |            |                  |            | <b>B</b> [blue]  |
|           |            |                  |            | <b>W</b> [white] |



**euro-conn**



**UL**  
 FILE N. E356435

**UNITS:** mm

**SHEET SIZE:** ISO A4

**SCALE:**

> 0 ~ 3

> 3 ~ 18

> 18 ~ 50

> 50 ~ 120

± 0.12

± 0.15

± 0.3

± 0.5



First angle projection

**HEADER**