





MATERIAL

- 1.Housing Material: Glass Filled Polyester UL94V-0 PBT, Nylon
- 2.Housing Color: Black or others
- 3.Contact Material: Phosphor Bronze $\Phi 0.46\text{mm}$
- 4.Plating: Gold plating over nickel. Gold plating thickness 1.5u "/ 3u " / 6u " / 15u " / 30u " / 50u "
- 5.Shield: 0.23 Thickness Brass with nickel plated

ELECTRICAL

- 1.Current Rating: 1.5 Amp
- 2.Voltage Rating: 125VAC
- 3.Contact Resistance: 30 M Ω Max.
- 4.Insulation Resistance: 500 M Ω Min. @ 500 VDC
- 5.Withstanding Voltage: 1000VAC RMS 50Hz 1 minute

MECHANICAL

- 1.Durability: 750 cycles Min.
- 2.PCB Retention pre-solder: 1 LB Min.

ENVIRONMENTAL

- 1.Storage: -40°C ~ +80°C
- 2.Operation: -40°C ~ +70°C

General description of ordering code

FAMILY	POSITIONS	CONTACTS	VERSION	TYPE	CLIP PLATING	OPTION	FRONT-SHIELD
MJS	8	8	N [SMT right angle]	H	F [flash gold]	S1 [split peg]	0 [without]
					S [gold 6u]		
					G [gold 15u]		



euro-conn



UNITS: mm

SHEET SIZE: ISO A4

SCALE: ----

> 0 ~ 3

> 3 ~ 18

> 18 ~ 50

> 50 ~ 120

± 0.12

± 0.15

± 0.3

± 0.5

! I prodotti e le caratteristiche possono cambiare senza preavviso.
The products and their features may change without notice.

MODULAR