



Specification:

GPS Antenna

Center Frequency: 1575.42±3MHz

Band Width:CF±5MHz

Polarization:RHCP

Gain:5dBic

V.S.W.R:<1.5

Impedance:50Ω

Axial Ratio:3dB (max)

LAN

Gain:28±2dB

Noise Figure:<1.5

Filter Insertion Loss:<3dB

Ex-band Attenuation:12dB@CF+50MHz/16dB@CF-50MHz

Supply Voltage:2.2~5V DC

Current Consumption:5~15mA

V.S.W.R:<2.0

GSM Antenna

Frequency Range: 824 ~ 960MHz/1710 ~ 2170MHz

V.S.W.R:<2.0

Polarization:Linear

Gain: 2.0dBi Max.

Impedance:50Ω

Cable:RG174

Connector:SMA/MCX/FAKRA or others

Radome Material:ABS

Mounting Method:Magnet

Operating Temperature :-40℃ ~ +85℃

General description of ordering code

FAMILY	MODEL	TYPE
ATR	- COMBO	SMAXXX*



euro-conn



UNITS: mm

SHEET SIZE: ISO A4

SCALE: ----

> 0 ~ 3

> 3 ~ 18

> 18 ~ 50

> 50 ~ 120

± 0.12

± 0.15

± 0.3

± 0.5

! I prodotti e le caratteristiche possono cambiare senza preavviso.
The products and their features may change without notice.

GPS + GSM ANTENNA