



**Technical parameters:**  
 Contact resistance: 0.03Ω, max  
 Insulation resistance: 100MΩ, min  
 Pressure: AC500V (50Hz) / 1minute  
 Rated Load: DC30V, 1.0A  
 Actuating Force: 3~20N  
 Life: 5000 times  
 Operating Temperature: -30°C ~ 70°C

**Material:**

Housing Material: PBT or PA66  
 Center Pin Material: Brass

Part No.	d1 (mm)	d2 (mm)	L1 (mm)	L2 (mm)	L3 (mm)
2.1A	2.1	5.5	14.0	13.0	20.0
2.1B	2.1	5.5	9.0	13.0	20.0
2.5A	2.5	5.5	14.0	13.0	20.0
2.5B	2.5	5.5	9.0	13.0	20.0
1.35A	1.35	3.45	9.0	11.5	20.0
1.0A	1.0	3.8	9.0	11.5	20.0

PN: **JD102**



**euro-conn**



UNITS: mm

SHEET SIZE: ISO A4

SCALE: ----

> 0 ~ 3

> 3 ~ 18

> 18 ~ 50

> 50 ~ 120

± 0.12

± 0.15

± 0.3

± 0.5

! I prodotti e le caratteristiche possono cambiare senza preavviso.  
 The products and their features may change without notice.

**DC POWER**